

WWW.SGCCTV.COM.SG | TEL : 81985572  
ENQUIRY@CHOICECYCLE.COM.SG  
1 ROCHOR CANAL ROAD, SIM LIM SQUARE #02-08, SINGAPORE 188504



## DA168 METAL ACCESS CONTROL SYSTEM / DA188 METAL WEATHERPROOF ACCESS CONTROL SYSTEM

# USER MANUAL

### FEATURES:

- ✓ Low power consumption: less than 30mA standby current.
- ✓ Luminous keyboard: the night can also operate keyboard
- ✓ User capacity: support 2,000 users
- ✓ Independent password: can use password which irrelevant with the card to open the door
- ✓ User modification password: Users can revise the door password
- ✓ Search speed: charge to open the door time less than 0.1 S.
- ✓ Output short circuit protection: electric lock or alarm output circuit within 100 μS when shut down automatically output
- ✓ Wiegand output: With Wiegand output interface, Wg26 card number or Wg4 buttons output
- ✓ Usable keyboard delete card number: After card is lost, usable keyboard delete card
- ✓ Thoroughly eliminate safety lapses
- ✓ The demolition alarm: Illegal dismantling machine, built-in alarm sound buzzer
- ✓ The bell button and interface: key and circuit segregation, external any the doorbell.

### TECHNICAL PARAMETERS

Work Voltage.	DC9-28V.
Reading Range	3~8cm
Ambient Temperature	-25°C~60°C
Electricity lock output	≤3A
Output short circuit protection time	≤100Ms
Size : 120 *56*18mm	120 *56*18mm
Static Current	≤30mA
Capacity	2000 users
Ambient Humidity	10%~90%
Alarm output	≤20A
Open time	0 ~ 99 seconds (adjustable)

